

2.1 Data Loader (dataloader)

- Introduction
- Command Line
 - Required Options
 - Optional Options
 - Example
- Deployment

Introduction

The Data Loader utility loads deployment-specific certificates, keystores, DNS entries, and Agent settings into a specified Direct Java RI Configuration Service.

The user is required to specify the target deployment domain and domain IPv4 address at runtime, as explained below.

Command Line

The utility is invoked on the command line:

```
$ ./dataloader.sh --help
Usage:
dataloader [--help -d <name> --dip <address> -i <path> --wsh <name> --wspd <path> --wsp <num>]
--help                                         Print help information.
-d (--domain) name                           Domain name to load data for.
--dip (--domainip) address                   Domain IPv4 address to load data for.
-i (--in) path                                Path to the input directory or archive file from which to read
certificates/keys.
--wsh (--wshost) name                        Web service (config-service) host.
--wspd (--wspath) path                         Web service (config-service) path.
--wsp (--wsport) num                          Web service (config-service) port number.
```

Required Options

-d (--domain) name
--dip (--domainip) address

Domain name to load data for.
Domain IPv4 address to load data for.

Optional Options

-i (--in) path Path to the input directory or archive file from which to read
certificates/keys.

- The default value of the -i (--in) option is: <script path>/..out/datagen/<domain>-data.zip

--wsh (--wshost) name Web service (config-service) host.

- The default value of the --wsh (--wshost) option is: <domain name>

--wspd (--wspath) path Web service (config-service) path.

- The default value of the --wspd (--wspath) option is: /config-service/ConfigurationService

--wsp (--wsport) num Web service (config-service) port number.

- The default value of the --wsp (--wsport) option is: 8081

Example

```
$ ./dataloader.sh -d localhost --dip 127.0.0.1
Connected to data service (http://localhost:8081/config-service/ConfigurationService).
Loaded 27 entries into data service (http://localhost:8081/config-service/ConfigurationService).
Loaded 5 setting(s) into data service (http://localhost:8081/config-service/ConfigurationService).
Loaded 54 DNS record(s) into data service (http://localhost:8081/config-service/ConfigurationService).
```

Deployment

- **Note:** The Data Loader utility always performs a minimum amount of changes.
 - It will only add new data entries if an identical entry does not already exist.
 - It will only modify existing data entries when/if they match the associated *key* (i.e. the domain name for a DNS A record) of a loading entry, but not its value.